Marauder SL

EXPECT MORE. CHOOSE READING.

Move More Payload



TOUGH I DURABLE I RELIABLE

- MORE payload capacity
- EASY to clean understructure
- SHIP-THRU design





SL Dump Body

The Marauder SL Dump was designed for maximum payload and increased fuel efficiency. The trapezoidal crossmemberless understructure provides better floor support and limits uneven deformation in the floor plate. The understructure design also allows the body to be washed down easier, eliminating road salts and other pre-wetting corrosives. The product receives Reading's exclusive 12 stage emersion prime process and durable abrasion resistant polyester powder coat finish. The Marauder SL is backed by Reading's three year limited warranty on body and hoist.

Features

Heavy-Duty Understructure

- 7 gauge trapezoidal longsills
- Crossmemberless understructure

Side Wall Construction

- 12 gauge sides
- Road spray rail
- Dirt-shedding top rail
- Equipped with sideboard gussets
- Full depth rear apron with rubber isolated clearance lights
- Full depth rear corner post with "banjo eye" chain holders and tarp tension bar receivers

Rugged Steel Floor

- Two piece HRA1011 steel floor plate
- Angled sidewalls to floor to eliminate bridging of material

High Capacity Hoist

- NTEA Class 30 double-acting, 12 volt, electric-hydraulic hoist and sub-frame assembly
- 8-13 Ton capacity, 50° dump angle
- Equipped with a safety body prop
- Grease zerks for ease of service and lubrication at all wear points

Protective Steel Bulkhead & Cab Shield

- Ship-Thru design
- 1/4 cab shield with window and tarp tension bar retainer

Reliable, Convenient Tailgate

- 12 gauge steel
- Double-wall construction with upper and lower formed box sections
- Single lever "fast-action" drop down tailgate release
- Forward tailgate release with adjustable linkage
- Upper gate pins equipped with grease zerks for ease of maintenance

Prep / Finish

- E-coat priming process
- Powder coat finish Black

Warrantv

3 year limited warranty on body and hoist



SL Dump Body and Hoist Specifications

PART NUMBER	MODEL	COLOR	C.A.	LENGTH	WIDTH	SIDES	ENDS	CAP (YDS)	LIFT CAP (YDS)
13600280	GM, Ford, Ram	BLACK	60"	9'0"	87"	16"	22"	2-4	11.6
13600080	GM, Ford, Ram	PRIME	60"	9'0"	87"	16"	22"	2-4	11.6
13600281	GM, Ford, Ram	BLACK	84"	11'0"	87"	16"	22"	3-4	9.3
13600081	GM, Ford, Ram	PRIME	84"	11'0"	87"	16"	22"	3-4	9.3



Locations Abington, PA Bowmansville, PA Clinton, MD

Columbus, OH Louisville. KY Pontiac, MI

Reading, PA Seneca, PA Suffolk, VA

SOLD AND SERVICED LOCALLY BY

All dimensions subject to plus or minus tolerance of 1/4" and all dimensions and all specifications are subject to change without notice An uniteristic souper, to plus of minus of earlier of 174 and an uniteristic sint an specifications are souper, to plus of minus of earlier of the and an uniteristic sint an specifications are souper, to plus of minus of the are optional. A luma-fill, Auto-Chock, Dual-Pro, Ztend-A-Sheff, Grip-n-Gilde, Latch-Matic, Ma-rauder, Reading, Redi-Dek, Rhino Linings, Rugged American, S.M.A.R.T. Racks, Spacemaker, Tool-Mates, and TUFF STUFF are registered trademarks of The Reading Group, LLC in the United States and some foreign countries. The Reading Kangaroo is a trademarked image and may not be reproduced or used without express permission from The Reading Group. RTB12-MSL-5M-07

www.ReadingBody.com

©2012 The Reading Group, LLC